


EXEGON PRO-DUTY

OMEGA MAJOR3630 BATTERY CHARGER

Features:-

- Microprocessor controlled
- Start routine includes self test
- Input voltage 220/240v 50Hz
- Output voltage 36v
- Output current 30A
- 3 stage charging, CC - CV - float
- Proportional timing, $T/2 + 1hr$
- 7 LED status indication
- Reverse polarity protection
- Rugged steel case
- Short circuit protection
- Independent overrun timer
- Soft start current control
- Zero parasitic current
- 2mm Powder coated mild steel case



Options:-

- Input voltage 110/130v
- Output connector options
- Set for various battery types:-
Vented lead acid
Sealed lead acid
Gel
Lead calcium
- Temperature compensation
- Dual voltage with a manual switch

Applications include:- UPS, telecom, general back up and fire systems

Model	Input Voltage	Output (Volt/Amps)	Dimensions (L x W x H mm)	Weight (Kg)	Minimum Battery Size
OmegaMajor3630	220/240v 50Hz	36v 30A	260 x 450 x 260	33	120Ah

Chargers are CE marked to indicate compliance with the Electromagnetic Compatibility Directive (89/336/EEC) and amending directive (92/31/EEC) and also the Low Voltage Directive (73/23/EEC). Compliance is achieved by working to BS EN 55014 section 7.3.7.7 and BS EN 60-335-2-29.



Exegon Ltd
Unit 1-3 Poulson's Yard, Strattons Walk, Melksham, Wiltshire, SN12 6JL
Tel: (01225) 791805 - Fax: (01225) 791629
Web: www.exegon.com - Email: sales@exegon.com

